

## Trench Struts

**ISCHEBECK**  
**GIGANT**

Type	Adjustment	SWL	Weight
<b>GIGANT</b> with hook-type angle from HEB 140			
Gi-S 120	0,70 - 1,20 m	210,0 - 177,3 kN	26 kg
Gi-S 170	1,05 - 1,70 m	210,0 - 177,3 kN	32 kg
Gi-S 210	1,40 - 2,10 m	184,4 - 156,1 kN	36 kg
Gi-S 260	1,90 - 2,60 m	176,3 - 139,7 kN	40 kg
Gi-S 310	2,40 - 3,10 m	156,8 - 138,1 kN	45 kg
Gi-SV 210	1,40 - 2,10 m	548,0 - 290,0 kN	69 kg
Gi-SV 260	1,90 - 2,60 m	471,0 - 260,0 kN	81 kg
Gi-SV 310	2,40 - 3,10 m	424,0 - 270,0 kN	92 kg
Gi-SV 380	3,10 - 3,80 m	390,0 - 258,0 kN	107 kg
Gi-SV 450	3,80 - 4,50 m	344,0 - 262,0 kN	122 kg

Type	Adjustment	SWL	Weight
<b>TITAN</b> with bearing angle for 140/160 mm			
Titan 48/120	0,70 - 1,17 m	63 - 48 kN	9 kg
Titan 48/150	0,90 - 1,50 m	61 - 45 kN	10 kg
Titan 48/210	1,20 - 2,10 m	60 - 38 kN	13 kg
Titan 60/150	0,90 - 1,50 m	100 - 99 kN	17 kg
Titan 60/200	1,40 - 2,00 m	100 - 93 kN	19 kg
Titan 60/250	1,90 - 2,50 m	95 - 84 kN	22 kg
Titan 60/300	2,40 - 3,00 m	85 - 72 kN	25 kg

Type	Adjustment	SWL	Weight
<b>TERRA</b> with claw plate and nail hole			
Terra 1	0,50 - 0,80 m	38 - 30 kN	3,60 kg
Terra 1a	0,60 - 0,90 m	36 - 29 kN	3,90 kg
Terra 2	0,80 - 1,10 m	34 - 29 kN	4,50 kg
Terra 3	1,10 - 1,40 m	29 - 23 kN	5,40 kg
Terra 4	1,40 - 1,70 m	26 - 22 kN	6,40 kg

